




DRILL CHART: TOP TO BOTTOM					
ALL UNITS ARE IN MILS					
FIGURE	SIZE	TOLERANCE	PLATED	QTY	
•	12.0	+3.0/-3.0	PLATED	24	25
•	13.0	+3.0/-3.0	PLATED	205	26
•	15.0	+3.0/-3.0	PLATED	79	27
*	39.0	+3.0/-3.0	PLATED	7	28
◊	41.0	+3.0/-3.0	PLATED	6	29
•	45.0	+3.0/-3.0	PLATED	12	30
▲	64.96	+3.0/-3.0	PLATED	8	31
○	75.0	+3.0/-3.0	PLATED	4	32
○	87.0	+2.0/-2.0	NOT PLATED	101	33
□	136.0	+2.0/-2.0	NOT PLATED	2	34
○	156.0	+2.0/-2.0	NOT PLATED	4	35
○	200.0x150.0	+5.0/-5.0	NOT PLATED	2	36
○	200.0x150.0	+5.0/-5.0	NOT PLATED	2	37



Drill: 200x150\_X2  
Rotated: 30°

Drill: 200x150\_X2  
Rotated: -30°

30.0° [30.0]

30.0° [30.0]

ARTWORK NO.	REV LEVEL	DESCRIPTION	NOM. LINE WIDTH/SPACING AND IMPEDANCE - +/-10%	
			LINE WIDTH/OHMS SINGLE ENDED	LINE WIDTH/SPAC/OHMS DIFFERENTIAL PAIRS
		TOP SILKSCREEN	N/A	N/A
		TOP SOLDER MASK	N/A	N/A
		TOP SOLDER PASTE	N/A	N/A
		LAYER 1 TOP	N/A	N/A
		LAYER 2 ONS	N/A	N/A
		LAYER 3 VCC	N/A	N/A
		LAYER 4 BOTTOM	N/A	N/A
		BOTTOM SOLDER PASTE	N/A	N/A
		BOTTOM SOLDER MASK	N/A	N/A
		BOTTOM SILKSCREEN	N/A	N/A

DETAIL A  
SCALE: NONE

MIN. LINE WIDTH : 0.203MM/0.008IN.
SURFACE FINISH : IMMERSION GOLD
SMALLEST HOLE : 0.330MM/0.013IN
OVERALL DIM : 132x66mm
4 LAYERS

## CHANGES

**WARNING**

**WARNING**

THIS WORK AND THE INFORMATION IT CONTAINS ARE THE PROPERTY OF OTIS ELEVATOR COMPANY ("OTIS"). IT IS DELIVERED TO OTHERS ON THE EXPRESS CONDITION THAT IT WILL BE USED ONLY FOR, OR ON BEHALF OF, OTIS; THAT NEITHER IT NOR THE INFORMATION IT CONTAINS WILL BE REPRODUCED, DISCLOSED, IN WHOLE OR IN PART, WITHOUT THE PRIOR WRITTEN CONSENT OF OTIS; AND THAT ON DEMAND IT AND ANY COPIES WILL BE PROMPTLY RETURNED TO OTIS.

UNPUBLISHED WORK © OTIS ELEVATOR COMPANY  
ALL RIGHTS RESERVED.

 **Otis**  
A United Technologies Company

CAN FIXTURE  
CF-4A

DWG	DAA26800S1
-----	------------

OTIS ENGINEERING CENTER  
SHANGHAI, CT

DRWN	F.RUI A.GUD	ORIGINAL DATE 2009.04.13
CHK	M.FANG	
APPD	JO.KIM	SHEETS
AUTH	CADTA-000534	SHEET

DRAFTED IN ACCORDANCE  
WITH OTIS DOCUMENT 52847